

## **Tips and tricks about installing the SkyVent Lightpipe**

- 1) Locate the diffuser vertically from the roof to the ceiling in the desired location. Cut the opening for the Vent for a metal roof or simply remove a tile for a tiled roof as per the installation instructions roof mounted dome.**
- 2) Make sure the opening in the roof and the opening desired for the ceiling is as straight as possible, so the tube is with limited bends to the desired location in the house. (ideal for bathrooms, hallways, WIR etc)**



**3) Use the template on the pack to cut the exact opening into the gyprock or other ceiling finish.**

**4) Push the diffuser housing up from the inside of the room, it will automatically click into place with the spring loaded clips, make sure they are all pointed up when installing. Wind the diffuser up or down as required for ventilation.**

**5) Straighten/ tighten to remove the concertina tube compressions so the tube is taut. This reduces reflective loss and improves light quality. Push in reflective tube to top and screw or tape fix if desired to inside of flashing base of unit and to the outside of the bottom diffuser collar ( 100 mm collar protrusion above ceiling is provided- caution check for space to fit to a cathedral ceiling) .**



**6) Please note, the smaller the vertical drop height the better light. Over 1.8 metre drop between the roof and ceiling and the daylight quality starts to be reduced.**

**Congratulations you should have installed a great product that will give you many years of energy free benefit.**